

Dr. pen M8

USER MANUAL

PLEASE READ THE MANUAL BEFORE USE





Power Interface

Power/Speed Button

Scale Adjustment Ring

Needle Cartridges

How to operate


Wireless Model: Dr pen M8-W

The instrument used with both built-in battery or AC power

Wired Model: Dr pen M8-C

The instrument used with with AC power only

- 1.Plug in DC adaptor to the jack
- 2.Plug in DC adaptor to AC outlet
- 3.To charge the battery:Plug the adapter into an outlet and connect it to the power interface



1.Take out needle cartridge from the sterilized packaging

How to operate

- 2. Fitting slot of cartridge into the pen correctly, push needle cartridge horizontally up to the end.
- 3.Lock the needle cartridge by turning it to the
- 4.Turn the needle cartridge clockwise and then pull out horizontally if you want to remove it. (Fig1) 5.Start the device

Press the power button for 2-3 seconds to start or shut down the device.



(Fig1)



In order to protect the pen well,do not invert the instrument to prevent the liquid backflow



How to operate

Adjustment of needle length

Adjust the depth of needle by turning the scale adjustment ring. The depth of needle should be adjusted after start the pen.

Turn it clockwise,needle depth will be shorter Turn it counterclockwise,needle depth will be longer



Speed Display











The pen starts from low to high speed The speed changes once each time you press

Needle cartridge introduction













Product name: **Auto-stamp Motorized Meso Machine**

Model name: Dr pen M8 Adapter: 5V-1000mA

Package Weight: about 333g Package Size: 169*123*56mm

Packing List

Item	Quantity	
Hand Piece	1 pc	
Adapter	1 pc	
Manual	1 pc	
Power Cable	1 pc	
Needle Cartridge	2 pcs	



Precaution

0		Please be sure to read instructions before use and follow as described.			
	<u>^</u>	Do not apply it to the man as follow: 1.Who has said desease or bloody disease over 38°C 2.Who has allergy and hemophile 3.Who has mellergiand hemophile 4.Who has high internal heat 5.Who task high internal heat 5.Who to pallery visits hospital 6.Who takes medicines 7.Who is under 12 years old			
	0	Do not use it on the power other than AC 220V. It may cause fires or malfunction			
	0	Do not use it near the place with high temperature, dust or humidity (Near the humidifier). It may cause malfunction.			
	0	Do not repair, disassemble or after the controller and the body. It may cause malfunction.			
	0	Do not touch the device or detach the power cords with wet hands. It may cause electric shock.			
	0	Do not use the stripped cord or propped cord. It may cause fires(Be sure to replace it with another).			
	0	Do not use the propped cord which has crack or scares. It may cause scares on the skin.			
	0	When you don't use it for a long time, unplug it from the outlet.			
	0	Be sure to have an inspection for test. If any troubles are found, get it repaired.			
	0	No one other than the operator can touch it. It may cause accidents or malfunction.			

\sim	Alternating current	SN	Serial No		
	Direct current	Œ	CE mark		
Δ	Attention, consult accompanying documents	-	Manufacturer		
M	Date of manufacture	F	Floating applied part		



Warranty

The warranty period of device is 6 months. We offer repair to our products from the day they are purchased. If any of our products has damages or natural trouble. We offer repair or replacements

General maintenance

Make sure to inspect the device and adapter

Keep it with its power off. Wipe its surface out with a dry cloth

Keep it away from direct sunlight or high

Do not leave the measurement, repair or alter of the device to non-professional staff

When you use the device which has not been used for a long time, make sure to check if it works properly with safety